


This drawing, specifications, and concepts contained here in are the sole property of Dart Aerospace, and may not be reproduced or used in any fashion without the prior written permission of Dart Aerospace Eugene, OR.

REVISIONS					
REV	ECR	DESCRIPTION	DATE	INITIAL	APPROVED
A		CH'D TITLEBLOCK AND REVISION BLOCK.	8/3/2009	RJC	RW
B		CH'D T/N FROM AN8514-1, CH'D ENGRAVE NOTES.	8/3/2009	RJC	RW
C		ARM & -2 ADDED MISSING DIMS, CH'D SOME DIM PRECISION TO MATCH INFO REC'D. ADDED ASSY VIEW AND TABLE SHEET 4.	1/10/2011	RJC	SE
4	16-0046	UPDATED TO NEW STANDARDS. ADDED USED ON MODELS TO ALL DWG SHEETS. DELETED NOTES 1 & 2 SHEET 1. -2 CH'D MAT'L WAS 4140 IS 4140/4142, ADDED MISSING DIM'S 2X R.010 MAX, .14 & .10, .18, CH'D DIMS WAS .384-.379 IS 2X .383-.378, DELETED .024 X 45°. -3 CH'D MAT'L WAS 4140 Q&T IS 4140/4142 Q&T, CH'D DIM WAS .090 IS .09, WAS R.025 IS R.03. -4 CH'D MAT'L WAS 4140 IS 4140/4142, DELETED .077 ±.005, ADDED MISSING DIMS 1.84, .29. -7 CH'D MAT'L WAS 4140 IS 4140/4142, DELETED .077 ±.005, ADDED MISSING DIMS 1.84, R.31.	3/1/2016	RJC	JAG



NOTE:
REF. BELL T/N AN8514-1.







TITLE ADJUSTABLE SPANNER WRENCH	
DWG NO. RB AN8514-1	REV 4

ASSY QTY	ASSY QTY	B/O	Part #	UNIT QTY	Description	Material	B/O INFORMATION OR SPECIFICATIONS	PG.	UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES		
			-2	1	HANDLE	4140/4142		2	.XXX ± .005 FRACTIONS ± 1/8		
			-3	1	BOLT	4140/4142 Q & T		3	.XX ± .01 ANGLES ± 5°		
			-4	1	ARM	4140/4142		4	.X ± .1 SURFACES = 125°		
			-5	1	ARM	4140/4142		4	1. BREAK ALL SHARP EDGES .015 x 45° OR .015R		
			-6	1	ARM	4140/4142		4	2. DIMENSIONAL LIMITS APPLY AFTER PLATING		
			-7	1	ARM	4140/4142		5	3. INTERPRET DIM AND TOL PER ASME Y14.5M-2009		
									USED ON MODEL		
									BELL 212, 230, 407, 412, 430		
									SCALE	1:1	DATE
									6/26/2000		SHEET 1 OF 5

MAT'L		SPEC	
HEAT TREAT		DRAWN BY: COLE	
FINISH		CHECKED: DUERFELDT	
		OPPS APPR: ANDERSON	
		QA APPR: LINDSAY	
		APPROVED: GILBERT	

This drawing, specifications, and concepts contained here in are the sole property of Dart Aerospace, and may not be reproduced or used in any fashion without the prior written permission of Dart Aerospace Eugene, OR.

REVISIONS					
REV	ECR	DESCRIPTION	DATE	INITIAL	APPROVED
B		CH'D ENGRAVE NOTES.	8/3/2009	RJC	RW
C		-2 ADDED MISSING DIMS, CH'D SOME DIM PRECISION TO MATCH INFO REC'D.	1/10/2011	RJC	SE
4	16-0046	-2 CH'D MAT'L WAS 4140 IS 4140/4142, ADDED MISSING DIM'S 2X R.010 MAX. .14 & .10, CH'D DIMS WAS .384-.379 IS 2X .383-.378. DELETED .024 X 45°.	3/1/2016	RJC	JAG







(-2)

HANDLE

DART AEROSPACE	
TITLE ADJUSTABLE SPANNER WRENCH	
DWG NO. RB AN8514-1-2	REV 4
MAT'L 4140/4142	UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES
HEAT TREAT RC 22-32	.XXX $\pm .005$ FRACTIONS $\pm 1/8$
FINISH BLACK OXIDE	.XX $\pm .01$ ANGLES $\pm .5^\circ$
SPEC QMSI-6.2.2 REV D	.X $\pm .1$ SURFACES = 125 \checkmark
DRAWN BY: COLE	1. BREAK ALL SHARP EDGES .015 x 45° OR .015R
CHECKED: DUERFELDT	2. DIMENSIONAL LIMITS APPLY AFTER PLATING
OPPS APPR: ANDERSON	3. INTERPRET DIM AND TOL PER ASME Y14.5M-2009
QA APPR: LINDSAY	USED ON MODEL
APPROVED: GILBERT	BELL 212, 230, 407, 412, 430
SCALE 1:1	DATE 6/26/2000
SHEET 2 OF 5	

This drawing, specifications, and concepts contained here in are the sole property of Dart Aerospace, and may not be reproduced or used in any fashion without the prior written permission of Dart Aerospace Eugene, OR.

REVISIONS					
REV	ECR	DESCRIPTION	DATE	INITIAL	APPROVED
4	16-0046	-3 CH'D MAT'L WAS 4140 Q&T IS 4140/4142 Q&T, CH'D DIM WAS .090 IS .09, WAS R.025 IS R.03.	3/1/2016	RJC	JAG





(-3)
BOLT

DART AEROSPACE	
TITLE ADJUSTABLE SPANNER WRENCH	
DWG NO. RB AN8514-1-3	REV 4
MAT'L 4140/4142 Q & T HEAT TREAT FINISH BLACK OXIDE SPEC QMSI-6.2.2 REV D	
UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES .XXX ± .005 FRACTIONS ± 1/8 .XX ± .01 ANGLES ± 5° .X ± .1 SURFACES = 125✓	
1. BREAK ALL SHARP EDGES .015 x 45° OR .015R 2. DIMENSIONAL LIMITS APPLY AFTER PLATING 3. INTERPRET DIM AND TOL PER ASME Y14.5M-2009	
DRAWN BY: COLE	USED ON MODEL
CHECKED: DUERFELDT	BELL 212, 230, 407, 412, 430
OPPS APPR: ANDERSON	
QA APPR: LINDSAY	
APPROVED: GILBERT	
SCALE 4:1	DATE 6/26/2000
SHEET 3 OF 5	

This drawing, specifications, and concepts contained here in are the sole property of Dart Aerospace, and may not be reproduced or used in any fashion without the prior written permission of Dart Aerospace Eugene, OR.

REVISIONS					
REV	ECR	DESCRIPTION	DATE	INITIAL	APPROVED
B		CH'D ENGRAVE NOTES.	8/3/2009	RJC	RW
C		ADDED MISSING DIMS, CH'D SOME DIM PRECISION TO MATCH INFO REC'D. ADDED TABLE.	1/10/2011	RJC	SE
4	16-0046	-4 CH'D MAT'L WAS 4140 IS 4140/4142, DELETED .077 ±.005, ADDED MISSING DIMS 1.84, .29.	3/1/2016	RJC	JAG



AN P/N		DIMENSION	
		A ±.005	Ø B ±.003
RB AN8514-4	.09 PIN ARM	.060	.089
RB AN8514-5	.12 PIN ARM	.120	.121
RB AN8514-6	.19 PIN ARM	.190	.183


DART AEROSPACE	
TITLE ADJUSTABLE SPANNER WRENCH	
DWG NO. RB AN8514-1-4	REV 4
MAT'L 4140/4142	UNLESS OTHERWISE SPECIFIED
HEAT TREAT RC 22-32	DIMENSIONS ARE IN INCHES
FINISH BLACK OXIDE	.XXX ± .005 FRACTIONS ± 1/8
SPEC QMSI-6.2.2 REV D	.XX ± .01 ANGLES ± 5°
DRAWN BY: COLE	.X ± .1 SURFACES = 125✓
CHECKED: DUERFELDT	1. BREAK ALL SHARP EDGES
OPPS APPR: ANDERSON	.015 x 45° OR .015R
QA APPR: LINDSAY	2. DIMENSIONAL LIMITS APPLY
APPROVED: GILBERT	AFTER PLATING
SCALE 2:1	3. INTERPRET DIM AND TOL PER ASME Y14.5M-2009
DATE 6/26/2000	USED ON MODEL
SHEET 4 OF 5	BELL 212, 230, 407, 412, 430

(-4) (-5) (-6)

ARM

This drawing, specifications, and concepts contained here in are the sole property of Dart Aerospace, and may not be reproduced or used in any fashion without the prior written permission of Dart Aerospace Eugene, OR.

REVISIONS					
REV	ECR	DESCRIPTION	DATE	INITIAL	APPROVED
B		CH'D ENGRAVE NOTES.	8/3/2009	RJC	RW
C		ADDED MISSING DIMS, CH'D SOME DIM PRECISION TO MATCH INFO REC'D.	1/10/2011	RJC	SE
4	16-0046	-7 CH'D MAT'L WAS 4140 IS 4140/4142, DELETED .077 ±.005, ADDED MISSING DIMS 1.84, R.31.	3/1/2016	RJC	JAG



NOTE:
USE DXF.

DART AEROSPACE	
TITLE ADJUSTABLE SPANNER WRENCH	
DWG NO. RB AN8514-1-7	REV 4
MAT'L 4140/4142	UNLESS OTHERWISE SPECIFIED
TREAT RC 22-32	DIMENSIONS ARE IN INCHES
FINISH BLACK OXIDE	.XXX ± .005 FRACTIONS ± 1/8
SPEC QMSI-6.2.2 REV D	.XX ± .01 ANGLES ± 5°
DRAWN BY: COLE	.X ± .1 SURFACES = 125
CHECKED: DUERFELDT	1. BREAK ALL SHARP EDGES
OPPS APPR: ANDERSON	.015 x 45° OR .015R
QA APPR: LINDSAY	2. DIMENSIONAL LIMITS APPLY
APPROVED: GILBERT	AFTER PLATING
SCALE 2:1	3. INTERPRET DIM AND TOL PER ASME Y14.5M-2009
DATE 6/26/2000	USED ON MODEL
SHEET 5 OF 5	BELL 212, 230, 407, 412, 430

(-7)
ARM